











# ブーム (CW付) 定格総荷重表

		ブーム (CW付) .....	23
		24mブーム+SLジブ (CW付) .....	29
		45mブーム+SLジブ (CW付) .....	46
		ブーム【特殊伸縮】(CW付) .....	58
		31m特殊伸縮ブーム+SLジブ (CW付) .....	64



# SL-850RfII ブーム (CW付) 定格総荷重表




通常伸縮 カウンタウエイト付	ブーム	ジブ	アウトリガ 前方	作業範囲
-------------------	-----	----	-------------	------





[m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0
2.2	80.00#	40.00*	40.00*	38.00*					
2.5	71.00*	40.00*	40.00*	38.00*	35.00	14.00			
3.5	57.50*	40.00*	40.00*	38.00*	35.00	14.00	13.00		
4.5	48.00*	40.00*	40.00*	34.00	30.30	14.00	13.00	10.20	8.20
5.5	40.00	40.00*	37.00*	30.00	26.50	14.00	13.00	10.20	8.20
6.5	34.00	34.00	32.70	27.00	23.50	14.00	13.00	10.20	8.20
8.0		26.90	26.00	23.00	19.90	14.00	13.00	10.20	8.20
10.0			20.50	19.50	16.50	14.00	12.70	10.20	8.20
12.0			16.50	16.20	13.90	12.10	11.10	10.20	8.20
14.0				13.10	11.90	10.30	9.50	8.95	8.10
16.0				10.80	10.30	9.00	8.20	7.95	7.20
18.0					9.00	7.90	6.90	6.85	6.30
20.0					7.30	7.00	6.10	5.85	5.50
22.0						6.15	5.40	5.10	4.90
24.0						5.50	4.80	4.50	4.30
28.0						4.10	3.85	3.60	3.50
32.0							3.15	2.95	2.80
34.0							2.85	2.65	2.55
38.0								2.20	2.10
41.0									1.80
危険 角度 標準 フック	[°]	—	—	—	—	—	—	—	—
フック 質量	[kg]	80*/40	40*/35			35			
巻掛 本数	[本]	20*/10	10*/7			7	4		

(単位 : ton)

注 #: 前方左右各15°の旋回範囲のみ

## SL-850RfII ブーム (CW付) 定格総荷重表

通常伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  7.6m	作業範囲 
-------------------	---	----	---	--

 [m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0
2.3	75.00*	40.00*	40.00*	38.00*	35.00				
3.0	63.00*	40.00*	40.00*	38.00*	35.00	14.00			
4.0	52.00*	40.00*	40.00*	37.00*	32.50	14.00	13.00	10.20	
5.0	44.00*	40.00*	39.00*	32.00	28.30	14.00	13.00	10.20	8.20
6.0	37.00	37.00*	35.00	28.50	24.90	14.00	13.00	10.20	8.20
7.0		31.30	30.50	25.50	22.20	14.00	13.00	10.20	8.20
9.0		23.50	23.00	21.00	18.10	14.00	13.00	10.20	8.20
11.0			15.70	15.55	15.10	13.10	12.10	10.20	8.20
13.0			11.40	11.25	11.20	11.10	10.20	9.55	8.20
15.0				8.50	8.40	9.40	8.80	8.45	7.70
17.0					6.45	7.40	7.60	7.45	6.75
19.0					4.95	5.90	6.40	6.35	5.90
21.0						4.70	5.20	5.40	5.20
23.0						3.75	4.25	4.45	4.55
26.0						2.70	3.15	3.35	3.45
30.0							2.10	2.25	2.40
33.0							1.45	1.65	1.75
36.0								1.15	1.25
40.0									0.70
 危険 角度 標準 フック	[°]	—	—	—	—	—	—	—	—
 フック 質量	[kg]	830*/470	470*/330			330			
 巻掛 本数	[本]	20*/10	10*/7			7	4		

(単位 : ton)









# SL-850RfII ブーム (CW付) 定格総荷重表

通常伸縮 カウンタウエイト付	ブーム	ジブ	アウトリガ  7.2m	作業範囲 
-------------------	-----	----	-------------------	----------

[m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0
2.3	55.00*	40.00*	40.00*	38.00*	35.00				
3.0	55.00*	40.00*	40.00*	38.00*	35.00	14.00			
4.0	48.00*	40.00*	40.00*	37.00*	32.50	14.00	13.00	10.20	
5.0	40.00	40.00*	39.00*	32.00	28.30	14.00	13.00	10.20	8.20
6.0	33.10	33.10	33.10	28.50	24.90	14.00	13.00	10.20	8.20
7.0		28.60	28.60	25.50	22.20	14.00	13.00	10.20	8.20
9.0		21.30	21.05	20.90	18.10	14.00	13.00	10.20	8.20
11.0			14.25	14.10	14.10	13.10	12.10	10.20	8.20
13.0			10.35	10.20	10.15	11.10	10.20	9.55	8.20
15.0				7.65	7.60	8.55	8.80	8.45	7.70
17.0					5.80	6.70	7.20	7.45	6.75
19.0					4.40	5.35	5.80	6.00	5.90
21.0						4.20	4.75	4.95	5.20
23.0						3.35	3.85	4.05	4.20
26.0						2.35	2.80	3.00	3.10
30.0							1.80	2.00	2.10
33.0							1.20	1.40	1.50
36.0								0.90	1.00
危険 角度 [°]	—	—	—	—	—	—	—	—	13
標準 フック [ton]	80*/40	40*/35			35				
フック 質量 [kg]	830*/470	470*/330			330				
巻掛 本数 [本]	20*/10	10*/7			7	4			

(単位 : ton)

通常伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  6.5m	作業範囲 
-------------------	---	----	---	--

 [m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0
2.3	50.00*	40.00*	40.00*	38.00*	35.00				
3.0	50.00*	40.00*	40.00*	38.00*	35.00	14.00			
4.0	44.00*	40.00*	40.00*	37.00*	32.50	14.00	13.00	10.20	
5.0	36.00	36.00*	36.00*	32.00	28.30	14.00	13.00	10.20	8.20
6.0	30.70	30.70	30.70	28.50	24.90	14.00	13.00	10.20	8.20
7.0		26.50	26.50	25.50	22.20	14.00	13.00	10.20	8.20
9.0		17.80	17.60	17.45	17.45	14.00	13.00	10.20	8.20
11.0			11.95	11.85	11.80	12.90	12.10	10.20	8.20
13.0			8.65	8.55	8.50	9.45	10.20	9.55	8.20
15.0				6.35	6.30	7.20	7.70	7.90	7.70
17.0					4.75	5.60	6.10	6.30	6.75
19.0					3.50	4.40	4.90	5.05	5.20
21.0						3.40	3.95	4.15	4.25
23.0						2.65	3.10	3.30	3.45
26.0						1.70	2.20	2.40	2.50
30.0							1.25	1.45	1.60
33.0							0.70	0.90	1.00
 危険 角度 標準 フック	[°]	—	—	—	—	—	—	21	28
 標準 フック	[ton]	80*/40	40*/35			35			
 フック 質量	[kg]	830*/470	470*/330			330			
 巻掛 本数	[本]	20*/10	10*/7			7	4		

(単位 : ton)






# SL-850RfII ブーム (CW付) 定格総荷重表







通常伸縮 カウンタウエイト付	ブーム	ジブ	アウトリガ  5.4m	作業範囲 
-------------------	-----	----	-------------------	----------

[m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0	
[m]	2.3	50.00*	40.00*	40.00*	38.00*	35.00				
	3.0	50.00*	40.00*	40.00*	38.00*	35.00	14.00			
	4.0	42.00*	40.00*	40.00*	37.00*	32.50	14.00	13.00	10.20	
	5.0	33.90	33.90	33.90	32.00	28.30	14.00	13.00	10.20	8.20
	6.0	28.80	28.80	28.30	28.00	24.90	14.00	13.00	10.20	8.20
	7.0		21.05	20.80	20.65	20.60	14.00	13.00	10.20	8.20
	9.0		13.10	12.90	12.75	12.75	13.85	13.00	10.20	8.20
	11.0			8.80	8.65	8.65	9.65	10.15	10.20	8.20
	13.0			6.30	6.15	6.15	7.05	7.55	7.75	7.85
	15.0				4.50	4.45	5.30	5.75	5.95	6.05
	17.0					3.15	4.05	4.50	4.65	4.75
	19.0					2.10	3.00	3.50	3.70	3.80
	21.0						2.20	2.70	2.95	3.05
	23.0						1.55	2.05	2.25	2.35
	26.0						0.70	1.25	1.45	1.60
	30.0									0.75
	危険 角度 標準	[°]	—	—	—	—	—	10	31	37
フック	[ton]	80*/40	40*/35			35				
フック 質量	[kg]	830*/470	470*/330			330				
巻掛 本数	[本]	20*/10	10*/7			7	4			





(単位 : ton)
















## SL-850RfII ブーム (CW付) 定格総荷重表

通常伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  4.3m	作業範囲 
-------------------	---	----	---	--





 [m]	10.0	13.0	17.0	20.0	24.0	31.0	38.0	42.0	45.0	
 [m]	2.3	40.00*	40.00*	40.00*	38.00*	35.00				
	3.0	40.00*	40.00*	40.00*	38.00*	35.00	14.00			
	4.0	37.10*	37.00*	36.90*	36.80*	32.50	14.00	13.00	10.20	
	5.0	27.70	27.60	27.35	26.20	24.45	14.00	13.00	10.20	8.20
	6.0	19.60	19.50	19.25	19.10	18.60	14.00	13.00	10.20	8.20
	7.0		14.65	14.45	14.35	14.35	14.00	13.00	10.20	8.20
	9.0		9.25	9.05	8.95	8.90	9.90	10.15	10.05	8.20
	11.0			6.05	5.95	5.95	6.85	7.35	7.45	7.45
	13.0			4.20	4.10	4.05	4.90	5.35	5.55	5.65
	15.0				2.80	2.70	3.55	4.00	4.20	4.30
	17.0					1.60	2.60	3.00	3.20	3.30
	19.0					0.75	1.70	2.25	2.45	2.55
	21.0						1.00	1.55	1.75	1.90
	23.0							0.95	1.20	1.30
	 危険 角度	[°]	—	—	—	—	19	35	46	50
 標準 フック	[ton]	40*/35				35				
 フック 質量	[kg]	470*/330				330				
 巻掛 本数	[本]	10*/7				7	4			














(単位 : ton)





通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ 前方 	作業範囲 
-------------------	--	---	--	---















 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
	84	2.8	4.20	5.8	3.50	7.8	2.20	8.7
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.3	3.50	17.2	2.65	18.2	1.95	18.3	1.40
57	17.7	3.10	19.4	2.50	20.1	1.95		
51	20.4	2.75	21.8	2.30	22.2	1.90		
45	22.8	2.40	23.9	2.10				
39	24.9	1.95	25.8	1.95				
33	26.8	1.60	27.3	1.60				
28	28.1	1.40	28.3	1.40				
24	28.9	1.25						
18	29.9	1.10						
 危険 角度 標準 フック	[°]	14	27	47	61			
 フック 質量	[ton]	5.6						
 質量	[kg]	120						
 巻掛 本数	[本]	1						





















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	2.8	4.20	5.8	3.50	7.8	2.20	8.7	1.50
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.3	3.50	17.2	2.65	18.2	1.95	18.3	1.40
57	17.7	3.10	19.4	2.50	20.1	1.95		
51	20.4	2.75	21.8	2.30	22.2	1.90		
45	22.8	2.40	23.9	2.10				
39	24.9	1.95	25.8	1.95				
33	26.8	1.60	27.3	1.60				
28	28.1	1.40	28.3	1.40				
24	28.9	1.25						
18	29.9	1.10						
 危険 角度 標準 フック	[°]	14	27	47	61			
	[ton]	5.6						
	[kg]	120						
	[本]	1						















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	2.8	4.20	5.8	3.50	7.8	2.20	8.7	1.50
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.3	3.50	17.2	2.65	18.2	1.95	18.3	1.40
57	17.7	3.10	19.4	2.50	20.1	1.95		
51	20.4	2.75	21.8	2.30	22.2	1.90		
45	22.8	2.40	23.9	2.10				
39	24.9	1.95	25.8	1.95				
33	26.8	1.60	27.3	1.60				
28	28.1	1.40	28.3	1.40				
24	28.9	1.25						
18	29.9	1.10						
 危険 角度 標準 フック	[°]	14		27		47		61
 フック 質量	[ton]				5.6			
 巻掛 本数	[kg]				120			
	[本]				1			















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	2.8	4.20	5.8	3.50	7.8	2.20	8.7	1.50
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.3	3.50	17.2	2.65	18.2	1.95	18.3	1.40
57	17.7	3.10	19.4	2.50	20.1	1.95		
51	20.4	2.75	21.8	2.30	22.2	1.90		
45	22.8	2.40	23.9	2.10				
39	24.9	1.90	25.8	1.80				
33	26.8	1.45	27.3	1.45				
28	28.1	1.10	28.3	1.05				
24	28.9	0.90						
18	29.9	0.65						
 危険 角度 標準 フック	[°]	14	27	47	61			
	[ton]	5.6						
	[kg]	120						
	[本]	1						
















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	2.8	4.20	5.8	3.50	7.8	2.20	8.7	1.50
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.3	3.50	17.2	2.65	18.2	1.95	18.3	1.40
57	17.7	3.10	19.4	2.50	20.1	1.95		
51	20.3	2.30	21.8	2.10	22.2	1.90		
45	22.7	1.60	23.9	1.50				
39	24.8	1.00	25.7	1.00				
33	26.7	0.55	27.2	0.55				
 危険 角度	[°]	30		32		47		61
 標準 フック	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						













通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	2.8	4.20	5.8	3.50	7.8	2.20	8.7	1.50
78	6.4	4.20	9.2	3.45	11.0	2.20	11.6	1.50
72	9.9	4.20	12.4	3.05	13.9	2.10	14.3	1.45
66	13.2	3.95	15.4	2.75	16.6	2.00	16.7	1.45
62	15.2	3.15	17.2	2.65	18.2	1.95	18.3	1.40
57	17.5	2.15	19.3	1.90	20.1	1.75		
51	20.2	1.35	21.7	1.20	22.2	1.15		
45	22.7	0.55	23.9	0.50				
 危険 角度	[°]	43	43	43	47	61		
 標準 フック	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						
















通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---

 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00
60	18.9	2.10	21.6	1.65	23.2	1.30		
54	22.1	1.80	24.4	1.55	25.4	1.25		
49	24.5	1.65	26.5	1.45	27.1	1.25		
45	26.2	1.60	28.1	1.40				
39	28.6	1.45	30.0	1.35				
33	30.7	1.40	31.5	1.30				
27	32.4	1.35						
21	33.6	1.30						
17	34.3	1.30						
 危険 角度 [°]	16		29		48		65	
 標準 フック [ton]	5.6							
 フック 質量 [kg]	120							
 巻掛 本数 [本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---














 [m]	24.0							
	5		25		45		60	
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00
60	18.9	2.10	21.6	1.65	23.2	1.30		
54	22.1	1.80	24.4	1.55	25.4	1.25		
49	24.5	1.65	26.5	1.45	27.1	1.25		
45	26.2	1.60	28.1	1.40				
39	28.6	1.45	30.0	1.35				
33	30.7	1.40	31.5	1.30				
27	32.4	1.35						
21	33.6	1.25						
17	34.3	1.20						
 危険 角度 標準 フック	[°]	16	29	48	65			
 フック 質量	[kg]	5.6						
 巻掛 本数	[本]	120						
		1						

通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00
60	18.9	2.10	21.6	1.65	23.2	1.30		
54	22.1	1.80	24.4	1.55	25.4	1.25		
49	24.5	1.65	26.5	1.45	27.1	1.25		
45	26.2	1.60	28.1	1.40				
39	28.6	1.45	30.0	1.35				
33	30.7	1.40	31.5	1.30				
27	32.4	1.30						
21	33.6	1.05						
17	34.3	0.90						
 危険 角度 [°]	16		29		48		65	
 標準 フック [ton]	5.6							
 フック 質量 [kg]	120							
 巻掛 本数 [本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---









 [m]	24.0							
	5		25		45		60	
								
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00
60	18.9	2.10	21.6	1.65	23.2	1.30		
54	22.1	1.80	24.4	1.55	25.4	1.25		
49	24.5	1.65	26.5	1.45	27.1	1.25		
45	26.2	1.60	28.1	1.40				
39	28.6	1.45	30.0	1.35				
33	30.6	1.20	31.5	1.15				
27	32.3	0.80						
21	33.6	0.60						
17	34.3	0.45						
 危険 角度 標準 フック	[°]	16	29	48	65			
 フック 質量	[kg]			5.6				
 巻掛 本数	[本]			120				
				1				





# KATO SL-850RfII 24mブーム+SLジブ (CW付) 定格総荷重表
















通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---





[m]	24.0								
	5		25		45		60		
[°]									
[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00	
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00	
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00	
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00	
60	18.9	2.10	21.6	1.65	23.2	1.30			
54	22.1	1.80	24.4	1.55	25.4	1.25			
49	24.5	1.65	26.5	1.45	27.1	1.25			
45	26.2	1.30	28.0	1.20					
39	28.5	0.80	29.9	0.75					
34	30.2	0.45	31.2	0.45					
危険 角度 標準 フック	[°]	33		33		48		65	
フック 質量	[ton]	5.6							
巻掛 本数	[kg]	120							
	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---





[m]	24.0								
	5		25		45		60		
[°]									
[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	3.7	2.80	8.2	2.65	11.3	1.55	12.8	1.00	
78	7.8	2.75	12.1	2.35	14.7	1.45	15.8	1.00	
72	11.8	2.70	15.5	2.05	17.8	1.40	18.5	1.00	
66	15.5	2.50	18.6	1.85	20.6	1.35	21.0	1.00	
60	18.9	2.10	21.6	1.65	23.2	1.30			
54	21.9	1.40	24.3	1.20	25.4	1.15			
49	24.2	0.80	26.4	0.70	27.1	0.70			
47	25.1	0.60	27.2	0.50					
危険 角度 標準 フック	[°]	46		46		48		65	
フック 質量	[ton]	5.6							
巻掛 本数	[kg]	120							
	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55
63	19.6	1.05	23.7	0.70	25.9	0.55		
57	23.2	0.85	26.8	0.65	28.4	0.55		
51	26.5	0.75	29.6	0.60	30.6	0.55		
48	28.1	0.70	30.8	0.60				
42	31.0	0.60	33.1	0.55				
36	33.4	0.55	34.9	0.55				
31	35.2	0.55	36.1	0.55				
27	36.3	0.50						
21	37.7	0.50						
 危険 角度 標準 フック	[°]	17	30	48	63			
	[ton]	5.6						
	[kg]	120						
	[本]	1						
















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55
63	19.6	1.05	23.7	0.70	25.9	0.55		
57	23.2	0.85	26.8	0.65	28.4	0.55		
51	26.5	0.75	29.6	0.60	30.6	0.55		
48	28.1	0.70	30.8	0.60				
42	31.0	0.60	33.1	0.55				
36	33.4	0.55	34.9	0.55				
31	35.2	0.55	36.1	0.55				
27	36.3	0.50						
21	37.7	0.50						
 危険 角度 標準 フック	[°]	17		30		48		63
 フック 質量	[kg]				5.6			
 巻掛 本数	[本]				120			
					1			















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---

 [m]	24.0							
	5		25		45		60	
 [°]								
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55
63	19.6	1.05	23.7	0.70	25.9	0.55		
57	23.2	0.85	26.8	0.65	28.4	0.55		
51	26.5	0.75	29.6	0.60	30.6	0.55		
48	28.1	0.70	30.8	0.60				
42	31.0	0.60	33.1	0.55				
36	33.4	0.55	34.9	0.55				
31	35.2	0.55	36.1	0.55				
27	36.3	0.50						
21	37.7	0.50						
 危険 角度 標準 フック	[°]	17	30	48	63			
 フック 質量	[kg]			5.6				
 巻掛 本数	[本]			120				
				1				

通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---





 [m]	24.0								
	5		25		45		60		
 [°]									
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55	
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55	
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55	
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55	
63	19.6	1.05	23.7	0.70	25.9	0.55			
57	23.2	0.85	26.8	0.65	28.4	0.55			
51	26.5	0.75	29.6	0.60	30.6	0.55			
48	28.1	0.70	30.8	0.60					
42	31.0	0.60	33.1	0.55					
36	33.4	0.55	34.9	0.55					
31	35.2	0.55	36.1	0.55					
27	36.3	0.50							
23	37.3	0.50							
 危険 角度	[°]	22		30		48		63	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---

 [m]	24.0							
	5		25		45		60	
 [°]								
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55
63	19.6	1.05	23.7	0.70	25.9	0.55		
57	23.2	0.85	26.8	0.65	28.4	0.55		
51	26.5	0.75	29.6	0.60	30.6	0.55		
48	28.1	0.70	30.8	0.60				
42	31.0	0.60	33.1	0.55				
38	32.7	0.50	34.3	0.50				
 危険 角度	[°]	35	37	48	63			
 標準 フック	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						




















# SL-850RfII 24mブーム+SLジブ (CW付) 定格総荷重表





通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---

 [m]	24.0								
	5		25		45		60		
 [°]									
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	4.6	1.80	10.4	1.00	14.7	0.70	16.7	0.55	
78	9.3	1.75	14.5	0.95	18.3	0.65	19.8	0.55	
72	13.6	1.45	18.4	0.85	21.6	0.60	22.6	0.55	
66	17.7	1.20	22.0	0.75	24.5	0.60	25.1	0.55	
63	19.6	1.05	23.7	0.70	25.9	0.55			
57	23.2	0.85	26.8	0.65	28.4	0.55			
51	26.5	0.70	29.6	0.60	30.6	0.55			
48	28.1	0.50							
 危険 角度 標準 フック	[°]	46	48	48	63				
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50	
78	13.4	4.00	16.6	3.30	17.2	2.15	17.6	1.50	
72	19.8	3.55	22.1	2.75	22.9	2.05	22.6	1.45	
66	25.2	2.60	27.0	2.15	27.8	1.95	27.2	1.45	
63	27.6	2.25	29.3	1.95	29.9	1.80			
57	32.2	1.75	33.6	1.55	33.7	1.50			
51	36.4	1.40	37.4	1.30	37.4	1.25			
48	38.3	1.25	39.1	1.15					
42	41.8	0.95	42.3	0.95					
36	44.8	0.75	45.1	0.75					
30	47.3	0.55	47.4	0.55					
26	48.7	0.40							
 危険 角度 標準 フック	[°]	25		29		48		63	
 フック 質量	[kg]	5.6							
 巻掛 本数	[本]	120							
		1							









通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---

危険角度 標準フック フック質量 巻掛本数	[m]	45.0							
		5		25		45		60	
危険角度 標準フック フック質量 巻掛本数	[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50	
78	13.4	4.00	16.6	3.30	17.2	2.15	17.6	1.50	
72	19.8	3.55	22.1	2.75	22.9	2.05	22.6	1.45	
66	25.2	2.60	27.0	2.15	27.8	1.95	27.2	1.45	
63	27.6	2.25	29.3	1.95	29.9	1.80			
57	32.2	1.60	33.6	1.50	33.7	1.50			
51	35.9	0.95	37.2	0.90	37.2	0.90			
48	37.8	0.60	38.9	0.60					
危険角度	[°]	45	45	48	63				
標準フック	[ton]	5.6							
フック質量	[kg]	120							
巻掛本数	[本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---














ブーム長さ [m]	45.0							
	5		25		45		60	
危険角度 [°]								
	標準フック質量 [kg]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50
78	13.4	4.00	16.6	3.30	17.2	2.15	17.6	1.50
72	19.8	3.55	22.1	2.75	22.9	2.05	22.6	1.45
66	25.2	2.60	27.0	2.15	27.8	1.95	27.2	1.45
63	27.6	2.25	29.3	1.95	29.9	1.80		
57	31.8	1.45	33.3	1.35	33.8	1.35		
51	35.8	0.70	37.0	0.65	37.1	0.65		
48	37.8	0.40	38.8	0.40				
危険角度 [°]	47		47		48		63	
標準フック質量 [ton]	5.6							
フック質量 [kg]	120							
巻掛本数 [本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---














ブーム長さ [m]	45.0							
	5		25		45		60	
危険角度 [°]								
	標準フック質量 [kg]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50
78	13.4	4.00	16.6	3.30	17.2	2.15	17.6	1.50
72	19.8	3.55	22.1	2.75	22.9	2.05	22.6	1.45
66	25.2	2.30	27.0	2.10	27.8	1.95	27.2	1.45
63	27.2	1.85	29.3	1.65	29.9	1.65		
57	31.4	1.00	33.0	0.90	33.5	0.90		
53	34.3	0.50	35.7	0.45	35.9	0.45		
危険角度 [°]	52		52		52		63	
標準フック質量 [ton]	5.6							
フック質量 [kg]	120							
巻掛本数 [本]	1							





# KATO SL-850RfII 45mブーム+SLジブ (CW付) 定格総荷重表















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50	
78	13.4	4.00	16.6	3.30	17.2	2.15	17.6	1.50	
72	19.8	2.90	22.1	2.50	22.9	2.05	22.6	1.45	
66	24.2	1.70	26.2	1.50	27.2	1.45	27.2	1.45	
63	26.7	1.15	28.6	1.00	29.2	1.00			
 危険 角度 標準 フック	[°]	61	61	61	61	61	63		
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	6.4	4.00	10.1	3.50	11.3	2.20	12.2	1.50	
78	13.4	4.00	16.6	3.25	17.2	2.15	17.6	1.50	
72	18.9	2.15	21.0	1.90	22.4	1.60	22.6	1.45	
69	21.2	1.50	23.5	1.30					
 危険 角度 標準 フック	[°]	67	68	69	69	69	69		
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							











通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	21.5	2.65	24.7	1.90	26.5	1.35	26.6	1.00	
66	27.4	2.15	30.0	1.70	31.5	1.30	31.2	1.00	
63	30.1	1.85	32.6	1.50	33.7	1.25			
57	35.0	1.40	37.0	1.20	37.8	1.15			
51	39.6	1.10	41.2	1.00	41.5	0.95			
48	41.7	1.00	43.2	0.90					
42	45.4	0.80	46.6	0.75					
36	48.6	0.65	49.3	0.60					
30	51.3	0.45	51.4	0.45					
 危険 角度 標準 フック	[°]	28		28		48		63	
 標準 フック 質量	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							











通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---

 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	21.5	2.65	24.7	1.90	26.5	1.35	26.6	1.00	
66	27.4	2.15	30.0	1.70	31.5	1.30	31.2	1.00	
63	30.1	1.85	32.6	1.50	33.7	1.25			
57	35.0	1.40	37.0	1.20	37.8	1.15			
51	39.2	0.75	41.1	0.75	41.3	0.75			
48	41.0	0.55	42.9	0.50					
46	42.2	0.40							
 危険 角度 標準 フック	[°]	45		46		48		63	
 フック 質量	[ton]	5.6							
 質量	[kg]	120							
 巻掛 本数	[本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---















 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	21.5	2.65	24.7	1.90	26.5	1.35	26.6	1.00	
66	27.4	2.15	30.0	1.70	31.5	1.30	31.2	1.00	
63	30.1	1.85	32.6	1.50	33.7	1.25			
57	35.0	1.20	37.0	1.15	37.8	1.10			
51	38.9	0.60	40.9	0.55	41.2	0.55			
危険 角度 標準 フック	[°]	48		48		48		63	
フック 質量	[kg]	120							
巻掛 本数	[本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---















 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	21.5	2.65	24.7	1.90	26.5	1.35	26.6	1.00	
66	27.4	2.05	30.0	1.70	31.5	1.30	31.2	1.00	
63	30.1	1.55	32.6	1.45	33.7	1.25			
57	34.3	0.85	36.7	0.75	37.6	0.75			
54	36.4	0.50							
危険 角度 標準 フック	[°]	53		54		54		63	
フック 質量	[kg]	120							
巻掛 本数	[本]	1							

# KATO SL-850RfII 45mブーム+SLジブ (CW付) 定格総荷重表





通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---















 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	21.5	2.60	24.7	1.90	26.5	1.35	26.6	1.00	
66	26.3	1.55	29.7	1.25	31.3	1.15	31.2	1.00	
63	28.9	1.05	32.0	0.85	33.4	0.75			
 危険 角度 標準 フック	[°]	61	62		62		63		
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							





通常伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---















 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	7.4	2.80	12.4	2.60	15.0	1.50	16.0	1.00	
78	15.0	2.70	18.9	2.20	20.8	1.40	21.5	1.00	
72	20.8	1.90	24.4	1.50	26.5	1.30	26.6	1.00	
69	23.3	1.35	26.6	1.10					
 危険 角度 標準 フック	[°]	67	68		69		69		
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							





















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	
84	8.5	1.80	14.3	1.00	18.3	0.70	20.1	0.55	
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55	
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55	
66	29.0	1.00	33.0	0.70	35.2	0.55	35.4	0.55	
63	32.0	0.95	35.7	0.65	37.6	0.55			
57	37.7	0.80	40.5	0.60	41.9	0.50			
51	43.0	0.65	45.2	0.55	45.6	0.50			
48	45.4	0.60	47.3	0.55					
42	49.5	0.55	50.9	0.55					
36	52.9	0.50	53.6	0.50					
32	54.8	0.40	55.1	0.40					
 危険 角度 標準 フック	[°]	31		31		48		64	
 フック 質量	[ton]	5.6							
 質量	[kg]	120							
 巻掛 本数	[本]	1							















通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---





 [m]	45.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	8.5	1.80	14.3	1.00	18.3	0.70	20.1	0.55	
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55	
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55	
66	29.0	1.00	33.0	0.70	35.2	0.55	35.4	0.55	
63	32.0	0.95	35.7	0.65	37.6	0.55			
57	37.7	0.80	40.5	0.60	41.9	0.50			
51	43.0	0.60	45.2	0.55	45.6	0.50			
 危険 角度	[°]	48		48		48		64	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							











通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	45.0							
	5		25		45		60	
 [°]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
	84	8.5	1.80	14.3	1.00	18.3	0.70	20.1
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55
66	29.0	1.00	33.0	0.70	35.2	0.55	35.4	0.55
63	32.0	0.95	35.7	0.65	37.6	0.55		
57	37.7	0.80	40.5	0.60	41.9	0.50		
52	42.1	0.45	44.4	0.45	45.0	0.45		
 危険 角度 [°]	51		51		51		64	
 標準 フック [ton]	5.6							
 フック 質量 [kg]	120							
 巻掛 本数 [本]	1							











通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---




 [m]	45.0							
	5		25		45		60	
 [°]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
	84	8.5	1.80	14.3	1.00	18.3	0.70	20.1
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55
66	29.0	1.00	33.0	0.70	35.2	0.55	35.4	0.55
63	32.0	0.95	35.7	0.65	37.6	0.55		
57	37.7	0.65	40.5	0.60	41.9	0.50		
 危険 角度 [°]	55		55		55		64	
 標準 フック [ton]	5.6							
 フック 質量 [kg]	120							
 巻掛 本数 [本]	1							







通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---

[m]		45.0								
[°]		5		25		45		60		
[°]										
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	8.5	1.80	14.3	1.00	18.3	0.70	20.1	0.55		
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55		
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55		
66	29.0	1.00	33.0	0.70	35.2	0.55	35.4	0.55		
64	31.0	0.95	34.8	0.65	36.8	0.55				
危険 角度 標準 フック	[°]	63		63		63		64		
フック 質量	[kg]	120								
巻掛 本数	[本]	1								

通常伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---

[m]		45.0								
[°]		5		25		45		60		
[°]										
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	8.5	1.80	14.3	1.00	18.3	0.70	20.1	0.55		
78	16.3	1.50	21.3	0.95	24.5	0.60	25.7	0.55		
72	22.9	1.20	27.5	0.80	30.2	0.55	30.8	0.55		
70	25.0	1.10								
危険 角度 標準 フック	[°]	69		70		70		70		
フック 質量	[kg]	120								
巻掛 本数	[本]	1								

特殊伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ 前方 	作業範囲 
-------------------	---	----	---	--






 [m]	17.0	24.0	31.0	
 [m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	14.00	11.00	9.00
	10.0	13.00	9.25	7.65
	12.0	11.50	7.95	6.40
	14.0	10.40	6.85	5.45
	16.0		6.00	4.70
	18.0		5.30	4.10
	20.0		4.65	3.60
	22.0			3.20
	24.0			2.85
	27.0			2.45
 危険 角度	[°]	—	—	—
 標準 フック	[ton]		35	
 フック 質量	[kg]		330	
 巻掛 本数	[本]		4	

(単位 : ton)












# SL-850RfII ブーム【特殊伸縮】(CW付) 定格総荷重表

特殊伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  7.6m	作業範囲 
-------------------	--	----	--	---



 [m]	17.0	24.0	31.0	
 [m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	14.00	11.00	9.00
	10.0	13.00	9.25	7.65
	12.0	11.50	7.95	6.40
	14.0	10.40	6.85	5.45
	16.0		6.00	4.70
	18.0		5.30	4.10
	20.0		4.65	3.60
	22.0			3.20
	24.0			2.85
	27.0			2.45
	 危険 角度 標準 フック	[°]	—	—
 フック 質量	[kg]		35	330
 巻掛 本数	[本]		4	







(単位 : ton)

特殊伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  7.2m	作業範囲 
-------------------	---	----	---	--

 [m]	17.0	24.0	31.0	
 [m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	14.00	11.00	9.00
	10.0	13.00	9.25	7.65
	12.0	11.50	7.95	6.40
	14.0	10.40	6.85	5.45
	16.0		6.00	4.70
	18.0		5.30	4.10
	20.0		4.65	3.60
	22.0			3.20
	24.0			2.85
	27.0			2.45
 危険 角度	[°]	—	—	—
 標準 フック	[ton]		35	
 フック 質量	[kg]		330	
 巻掛 本数	[本]		4	




(単位 : ton)







特殊伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  6.5m	作業範囲 
-------------------	---	----	--	---

 [m]	17.0	24.0	31.0	
 [m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	14.00	11.00	9.00
	10.0	13.00	9.25	7.65
	12.0	11.50	7.95	6.40
	14.0	9.35	6.85	5.45
	16.0		6.00	4.70
	18.0		5.30	4.10
	20.0		4.65	3.60
	22.0			3.20
	24.0			2.85
	27.0			2.45
	 危険 角度	[°]	—	—
 標準 フック	[ton]		35	
 フック 質量	[kg]		330	
 巻掛 本数	[本]		4	

(単位 : ton)



特殊伸縮 カウンタウエイト付	ブーム 	ジブ	アウトリガ  5.4m	作業範囲 
-------------------	---	----	---	--

 [m]	17.0	24.0	31.0	
 [m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	14.00	11.00	9.00
	10.0	12.65	9.25	7.65
	12.0	9.30	7.95	6.40
	14.0	7.15	6.85	5.45
	16.0		6.00	4.70
	18.0		5.00	4.10
	20.0		4.15	3.60
	22.0			3.20
	24.0			2.85
	27.0			2.45
 危険 角度	[°]	—	—	—
 標準 フック	[ton]		35	
 フック 質量	[kg]		330	
 巻掛 本数	[本]		4	

(単位 : ton)





















# SL-850RfII ブーム【特殊伸縮】(CW付) 定格総荷重表





特殊伸縮 カウンタウエイト付	ブーム	ジブ	アウトリガ  4.3m	作業範囲 
-------------------	-----	----	-------------------	----------















[m]		17.0	24.0	31.0
[m]	2.5	14.00	13.00	9.00
	3.5	14.00	13.00	9.00
	4.5	14.00	13.00	9.00
	5.5	14.00	13.00	9.00
	6.5	14.00	12.70	9.00
	8.0	13.40	11.00	9.00
	10.0	9.25	9.25	7.65
	12.0	6.80	7.30	6.40
	14.0	5.20	5.65	5.45
	16.0		4.45	4.70
	18.0		3.60	4.10
	20.0		2.95	3.10
	22.0			2.60
	24.0			2.15
	27.0			1.60
	危険 角度	[°]	—	—
標準 フック	[ton]		35	
フック 質量	[kg]		330	
巻掛 本数	[本]		4	





(単位 : ton)















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	31.0								
	5		25		45		60		
 [°]									
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	
84	4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50	
78	8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50	
72	13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45	
66	17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45	
60	20.9	2.20	22.5	1.85	23.2	1.75			
54	24.2	1.70	25.5	1.50	25.8	1.50			
48	27.2	1.30	28.2	1.20	28.2	1.20			
45	28.5	1.15	29.4	1.10					
39	30.8	0.90	31.6	0.85					
33	32.9	0.70	33.4	0.70					
29	34.1	0.60	34.4	0.55					
24	35.5	0.50							
20	36.4	0.45							
 危険 角度 標準 フック	[°]	19		28		46		62	
 標準 フック 質量	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---





 [m]	31.0							
	5		25		45		60	
 [°]								
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50
78	8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50
72	13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45
66	17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45
60	20.9	2.20	22.5	1.85	23.2	1.75		
54	24.2	1.70	25.5	1.50	25.8	1.50		
48	27.2	1.30	28.2	1.20	28.2	1.20		
45	28.5	1.15	29.4	1.10				
39	30.8	0.90	31.6	0.85				
33	32.9	0.70	33.4	0.70				
29	34.1	0.60	34.4	0.55				
24	35.5	0.50						
20	36.4	0.45						
 危険 角度 標準 フック	[°]	19	28	46	62			
 フック 質量	[kg]					5.6		
 巻掛 本数	[本]					120		
						1		
















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	31.0								
	5		25		45		60		
 [°]									
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	
84	4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50	
78	8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50	
72	13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45	
66	17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45	
60	20.9	2.20	22.5	1.85	23.2	1.75			
54	24.2	1.70	25.5	1.50	25.8	1.50			
48	27.2	1.30	28.2	1.20	28.2	1.20			
45	28.5	1.15	29.4	1.10					
39	30.8	0.90	31.6	0.85					
33	32.9	0.70	33.4	0.70					
29	34.1	0.60	34.4	0.55					
24	35.5	0.50							
20	36.4	0.45							
 危険 角度	[°]	19		28		46		62	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---

危険角度 標準フック フック質量 巻掛本数	[m]	31.0							
		5		25		45		60	
危険角度 標準フック フック質量 巻掛本数	[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50	
78	8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50	
72	13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45	
66	17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45	
60	20.9	2.20	22.5	1.85	23.2	1.75			
54	24.2	1.70	25.5	1.50	25.8	1.50			
48	27.2	1.30	28.2	1.20	28.2	1.20			
45	28.5	1.15	29.4	1.10					
39	30.8	0.90	31.6	0.85					
33	32.9	0.70	33.4	0.70					
29	34.1	0.60	34.4	0.55					
24	35.5	0.50							
20	36.4	0.45							
危険角度	[°]	19		28		46		62	
標準フック	[ton]	5.6							
フック質量	[kg]	120							
巻掛本数	[本]	1							





特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---














 [m]	31.0								
	5		25		45		60		
 [°]									
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50	
78	8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50	
72	13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45	
66	17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45	
60	20.9	2.20	22.5	1.85	23.2	1.75			
54	24.2	1.70	25.5	1.50	25.8	1.50			
48	27.2	1.30	28.2	1.20	28.2	1.20			
45	28.5	1.15	29.4	1.10					
39	30.8	0.90	31.6	0.85					
33	32.9	0.70	33.4	0.70					
29	34.1	0.60	34.4	0.55					
24	35.5	0.50							
20	36.4	0.45							
 危険 角度	[°]	19		28		46		62	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  9.52m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---

危険角度 標準フック 質量 巻掛本数	[m]	31.0							
		5		25		45		60	
危険角度 標準フック 質量 巻掛本数	[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84		4.1	4.00	7.4	3.50	9.2	2.20	10.0	1.50
78		8.9	4.00	11.7	3.35	13.1	2.15	13.6	1.50
72		13.4	3.85	15.6	2.95	16.8	2.05	17.0	1.45
66		17.5	2.80	19.2	2.35	20.1	2.00	20.1	1.45
60		20.9	2.20	22.5	1.85	23.2	1.75		
54		24.2	1.65	25.5	1.50	25.8	1.50		
48		26.9	1.25	28.1	1.15	28.2	1.15		
45		28.2	1.05	29.3	1.00				
39		30.7	0.70	31.5	0.70				
34		32.6	0.45	33.1	0.45				
危険角度	[°]	33		33		46		62	
標準フック	[ton]	5.6							
質量	[kg]	120							
巻掛本数	[本]	1							







特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---





 [m]	31.0								
	5		25		45		60		
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00	
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00	
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00	
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00	
63	21.8	2.00	24.5	1.60	25.9	1.30			
57	25.5	1.55	27.9	1.30	28.8	1.20			
51	29.0	1.20	30.9	1.05	31.4	1.05			
45	32.0	0.95	33.5	0.90					
39	34.7	0.75	35.8	0.70					
33	37.0	0.55	37.7	0.55					
27	38.9	0.45							
22	40.2	0.40							
 危険 角度 標準 フック	[°]	21		29		47		63	
 標準 フック 質量	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							





















# SL-850RfII 31m特殊伸縮ブーム+SLジブ (CW付) 定格総荷重表

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---





危険角度 標準フック 質量 巻掛本数	[m]	31.0							
		5		25		45		60	
危険角度 標準フック 質量 巻掛本数	[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00	
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00	
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00	
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00	
63	21.8	2.00	24.5	1.60	25.9	1.30			
57	25.5	1.55	27.9	1.30	28.8	1.20			
51	29.0	1.20	30.9	1.05	31.4	1.05			
45	32.0	0.95	33.5	0.90					
39	34.7	0.75	35.8	0.70					
33	37.0	0.55	37.7	0.55					
27	38.9	0.45							
22	40.2	0.40							
危険角度	[°]	21		29		47		63	
標準フック	[ton]	5.6							
質量	[kg]	120							
巻掛本数	[本]	1							















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	31.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00	
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00	
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00	
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00	
63	21.8	2.00	24.5	1.60	25.9	1.30			
57	25.5	1.55	27.9	1.30	28.8	1.20			
51	29.0	1.20	30.9	1.05	31.4	1.05			
45	32.0	0.95	33.5	0.90					
39	34.7	0.75	35.8	0.70					
33	37.0	0.55	37.7	0.55					
27	38.9	0.45							
22	40.2	0.40							
 危険 角度	[°]	21		29		47		63	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							
















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---





危険角度 標準フック 質量 巻掛本数	[m]	31.0							
		5		25		45		60	
危険角度 標準フック 質量 巻掛本数	[°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00	
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00	
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00	
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00	
63	21.8	2.00	24.5	1.60	25.9	1.30			
57	25.5	1.55	27.9	1.30	28.8	1.20			
51	29.0	1.20	30.9	1.05	31.4	1.05			
45	32.0	0.95	33.5	0.90					
39	34.7	0.75	35.8	0.70					
33	37.0	0.55	37.7	0.55					
27	38.9	0.45							
22	40.2	0.40							
危険角度	[°]	21		29		47		63	
標準フック	[ton]	5.6							
質量	[kg]	120							
巻掛本数	[本]	1							















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---





 [m]	31.0							
	5		25		45		60	
	 [°]		 [°]		 [°]		 [°]	
 [°]	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00
63	21.8	2.00	24.5	1.60	25.9	1.30		
57	25.5	1.55	27.9	1.30	28.8	1.20		
51	29.0	1.20	30.9	1.05	31.4	1.05		
45	32.0	0.95	33.5	0.90				
39	34.7	0.75	35.8	0.70				
33	37.0	0.55	37.7	0.55				
27	38.9	0.45						
22	40.2	0.40						
 危険 角度	[°]	21	29	47	63			
 標準 フック	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  13.8m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---

 [m]	31.0							
	5		25		45		60	
 [°]								
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	5.3	2.80	10.1	2.60	12.9	1.55	14.1	1.00
78	10.5	2.75	14.5	2.25	17.0	1.45	17.8	1.00
72	15.4	2.70	18.8	2.00	20.8	1.35	21.2	1.00
66	19.8	2.30	22.7	1.75	24.3	1.30	24.4	1.00
63	21.8	2.00	24.5	1.60	25.9	1.30		
57	25.5	1.55	27.9	1.30	28.8	1.20		
51	29.0	1.20	30.9	1.05	31.4	1.05		
45	31.9	0.85	33.5	0.80				
39	34.6	0.55	35.8	0.55				
36	35.8	0.40						
 危険 角度	35		36		47		63	
 標準 フック					5.6			
 フック 質量					120			
 巻掛 本数					1			





特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  前方	作業範囲 
-------------------	--	---	--	---















 [m]	31.0							
	5		25		45		60	
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55
78	12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55
72	17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55
66	21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55
63	24.1	1.00	27.8	0.70	29.8	0.55		
57	28.4	0.80	31.4	0.65	32.9	0.55		
51	32.1	0.70	34.9	0.60	35.5	0.55		
48	33.9	0.65	36.4	0.55				
42	37.1	0.60	39.0	0.55				
36	39.9	0.50	41.1	0.50				
30	42.2	0.40	42.7	0.40				
 危険 角度 標準 フック	[°]	28	28	48	64			
 標準 フック 質量	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						





特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.6m	作業範囲 
-------------------	--	---	--	---















 [m]	31.0							
	5		25		45		60	
 [°]								
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]
84	6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55
78	12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55
72	17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55
66	21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55
63	24.1	1.00	27.8	0.70	29.8	0.55		
57	28.4	0.80	31.4	0.65	32.9	0.55		
51	32.1	0.70	34.9	0.60	35.5	0.55		
48	33.9	0.65	36.4	0.55				
42	37.1	0.60	39.0	0.55				
36	39.9	0.50	41.1	0.50				
30	42.2	0.40	42.7	0.40				
 危険 角度	[°]	28	28	48	64			
 標準 フック	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						





















特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  7.2m	作業範囲 
-------------------	--	---	--	---





 [m]	31.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55	
78	12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55	
72	17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55	
66	21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55	
63	24.1	1.00	27.8	0.70	29.8	0.55			
57	28.4	0.80	31.4	0.65	32.9	0.55			
51	32.1	0.70	34.9	0.60	35.5	0.55			
48	33.9	0.65	36.4	0.55					
42	37.1	0.60	39.0	0.55					
36	39.9	0.50	41.1	0.50					
30	42.2	0.40	42.7	0.40					
 危険 角度 標準 フック	[°]	28		28		48		64	
 標準 フック 質量	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							









特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  6.5m	作業範囲 
-------------------	--	---	--	---

 [m]	31.0								
	5		25		45		60		
 [°]									
	[m]	[ton]	[m]	[ton]	[m]	[ton]	[m]	[ton]	
84	6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55	
78	12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55	
72	17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55	
66	21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55	
63	24.1	1.00	27.8	0.70	29.8	0.55			
57	28.4	0.80	31.4	0.65	32.9	0.55			
51	32.1	0.70	34.9	0.60	35.5	0.55			
48	33.9	0.65	36.4	0.55					
42	37.1	0.60	39.0	0.55					
36	39.9	0.50	41.1	0.50					
30	42.2	0.40	42.7	0.40					
 危険 角度	[°]	28		28		48		64	
 標準 フック	[ton]	5.6							
 フック 質量	[kg]	120							
 巻掛 本数	[本]	1							

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  5.4m	作業範囲 
-------------------	--	---	--	---

 [m]	31.0							
	5		25		45		60	
 [°]								
	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84	6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55
78	12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55
72	17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55
66	21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55
63	24.1	1.00	27.8	0.70	29.8	0.55		
57	28.4	0.80	31.4	0.65	32.9	0.55		
51	32.1	0.70	34.9	0.60	35.5	0.55		
48	33.9	0.65	36.4	0.55				
42	37.1	0.60	39.0	0.55				
36	39.9	0.50	41.1	0.50				
30	42.2	0.40	42.7	0.40				
 危険 角度 標準 フック	[°]	28	28	48	64			
 標準 フック 質量	[ton]	5.6						
 フック 質量	[kg]	120						
 巻掛 本数	[本]	1						

特殊伸縮 カウンタウエイト付	ブーム 	ジブ  18.0m	アウトリガ  4.3m	作業範囲 
-------------------	--	---	--	---

危険角度 標準フック フック質量 巻掛本数	[°] [ton] [kg] [本]	31.0							
		5		25		45		60	
		 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]	 [m]	 [ton]
84		6.2	1.80	12.1	1.00	16.2	0.70	18.0	0.55
78		12.0	1.65	17.1	0.95	20.5	0.65	21.9	0.55
72		17.3	1.25	21.6	0.85	24.5	0.60	25.4	0.55
66		21.8	1.10	26.0	0.75	28.1	0.55	28.6	0.55
63		24.1	1.00	27.8	0.70	29.8	0.55		
57		28.4	0.80	31.4	0.65	32.9	0.55		
51		32.1	0.70	34.9	0.60	35.5	0.55		
48		33.9	0.65	36.4	0.55				
42		37.1	0.55	39.0	0.50				
		38		38		48		64	
		5.6							
		120							
		1							